

TPa - přebytky výroby k 1.7.24 skladem

ks	typ	parametry			
	(kód výrobku)	průměr (mm)	délka (mm)	délka vývodů (mm)	napětí (V)
2	12503/1810E	9,52	200	300	230
2	12307/9780E	20	130	300	110
1	12307/5590E	18,2	145	500	260
1	12503/8450E	9,25	255	1150	230
1	12503/7940E	9,8	400	600	220
2	12503/4240E	9,8	300	300	110
1	12503/3870E	9,8	200	300	220
6	12503/4220E	10	100	1000	240
15	12503/3200E	10	90	1000	240
3	12302/1680E	8	65	900	230
1	12510/4290E	18	300	500	230
1	12310/9740E	17	350	500	230
4	12503/8830E	10	430	0	230
1	12407/9310E	19,85	450	1300	230
1	12510/5860E	19	61	1000	240
2	12503/7910E	10	74	300	230
1	12504/8380E	12	35	250	220
2	12304/4190E	12	35	1000	220
3	12303/4250E	10	70	600	230
1	12302/7790E	8	100	500	230
1	12301/8410E	6	115	500	230
1	12302/7420E	8	80	1000	230
1	12302/7230E	8	80	350	230
1	12301/8000E	6,5	80	500	230
1	12302/7930E	8	60	700	230
1	12301/8480E	6,5	80	1300	230
1	12301/6060E	6,5	55	500	230
1	12301/7400E	6	40	500	230
1	12301/0560E	6,5	60	300	230
1	12301/7800E	6,5	60	250	24
1	12301/1190E	6,5	60	300	230
8	12503/9150E	10	105	1000 /kov. hadice/	48
1	12503/2580E	10	615	300	230
3	12410/7720E	17	600	500	400
3	12604/1080E	12,5	160	250	230
2	12510/6130E	16	216 R	600 /plast. hadice/	230

příkon (W)
1000
600
750
650
800
500
500
150
70
50
1000
490
450
3200
150
500
100
100
120
200
300
300
250
200
300
120
300
80
125
20
250
400
600
850
160
400